

MODEL: SHUTTLE™ 6

TYPE: ELECTRIC POWERED PERSONNEL CARRIER

MODEL YEAR: 2012

Part No:. 618852



PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

Precision Drive System™ (PDS): Factory programmable to application

- Solid State continuously variable seperately excited speed controller
- Dash mounted direction selector switch (Forward-Neutral-Reverse)
- Anti-roll back, walkaway braking and alarm
- Anti-stall motor protection
- Regenerative 'Pedal Down' and/or 'Pedal Up' braking
- Eight, 6 Volt Deep Cycle
- Full torque, reduced speed reverse
- Inductive throttle sensor
- Diagnostic indicator
- Factory selectable performance options

Battery Charger: Delta Q, 48 VDC. H120/230 VAC 50/60 Hz. Underwriters Laboratories (U.L.) Listed, (C.S.A. Certified)

48 volt DC shunt wound, brazed armature, solid copper windings. Intermittant Horsepower 18.1 hp (13.5 kW) at 1900 rpm (1hour) Motor:

Drive Train: Direct motor shaft connected to transaxle pinion shaft

Electrical System: 48 Volt DC, eight, 6 volt deep cycle storage batteries (107 minute, 225 amp-hour @ 20 hr. discharge rate)

Transaxle: Differential with helical gears

Dual rear wheel mechanical self-adjusting drum brakes. Automatic single point park brake release with self-compensating system Brakes:

PRODUCT OVERVIEW				
	Performance			
136.0 in (345 cm)	Seating Capacity	6 Person		
48.5 in (123 cm)	Dry Weight	720 lb (325 kg) (Without Batteries)		
48.6 in (123 cm) (Top of steering wheel)	Curb Weight	1210 lb (545 kg)		
72.0 in (183 cm)	Vehicle load capacity	1198 lb (540 kg)		
93.5 in (237 cm)	Outside Clearance Circle	25.5 ft (7.8 m)		
34.2 in (86.7 cm)	Speed (Level Ground)	13 mph \pm 0.5 mph (21 kph \pm 0.8 kph)		
38.0 in (97 cm)	Towing Capacity	N/A		
4.3 in (11 cm)	Steering & Suspension			
	Steering	Self-compensating rack and pinion		
48 Volts DC	Front Suspension	Leaf springs with hydraulic shock absorbers		
Shunt Wound	Rear Suspension	Leaf springs with hydraulic shock absorbers		
2.5 hp (1.9 kW)	Service Brake	Rear wheel mechanical self-adjusting drum		
18.1 hp (13.5 kW) @ 1900 rpm	Parking Brake	Self-compensating, single point engagement		
48 Volt	Front Tires	Links 18 x 8.50 - 8 (4 Ply Rated)		
Eight, 6 Volt Deep Cycle	Rear Tires	Links 18 x 8.50 - 8 (4 Ply Rated)		
Pedal Start	Body & Chassis			
48 VDC Delta Q, 120/230 VAC, UL & CSA	Frame	Welded steel. DuraShield™ powder coat		
400 Amp Precision Drive System (PDS)	Body & Finish	Injection molded TPO		
Motor Shaft Direct Drive	Seat Pod	Fiberglass & Gelcoat		
Differential with helical gears	Standard Color	Patriot Blue		
Dash Mounted Forward-Neutral-Reverse				
14.7:1				
	136.0 in (345 cm) 48.5 in (123 cm) 48.6 in (123 cm) (Top of steering wheel) 72.0 in (183 cm) 93.5 in (237 cm) 34.2 in (86.7 cm) 38.0 in (97 cm) 4.3 in (11 cm) 48 Volts DC Shunt Wound 2.5 hp (1.9 kW) 18.1 hp (13.5 kW) @ 1900 rpm 48 Volt Eight, 6 Volt Deep Cycle Pedal Start 48 VDC Delta Q, 120/230 VAC, UL & CSA 400 Amp Precision Drive System (PDS) Motor Shaft Direct Drive Differential with helical gears Dash Mounted Forward-Neutral-Reverse	Performance 136.0 in (345 cm) 48.5 in (123 cm) 48.6 in (123 cm) (Top of steering wheel) 72.0 in (183 cm) 93.5 in (237 cm) 34.2 in (86.7 cm) 38.0 in (97 cm) 4.3 in (11 cm) Steering & Suspension Steering 48 Volts DC Shunt Wound 2.5 hp (1.9 kW) 18.1 hp (13.5 kW) @ 1900 rpm 48 Volt Eight, 6 Volt Deep Cycle Pedal Start 48 VDC Delta Q, 120/230 VAC, UL & CSA 400 Amp Precision Drive System (PDS) Motor Shaft Direct Drive Dash Mounted Forward-Neutral-Reverse Pedal Stand Pry Meight Curb Weight Vehicle load capacity Vehicle load capacity Outside Clearance Circle Speed (Level Ground) Towing Capacity Steering & Suspension Steering Front Suspension Service Brake Parking Brake Front Tires Rear Tires Body & Chassis Frame Body & Frame Seat Pod Standard Color		

Some items shown may be optional equipment



Item	Std Opt Fld	Item	Std Opt
TIRES & WHEELS:		ELECTRICAL:	
Front:		Battery Chargers:	
Links 18 x 8.50 - 8 (4 Ply Rated)	•	48 VDC PowerWise™, 230 VAC, 50 Hz	•
USA Trail 18 x 8.50 - 8 (Load Range C)	•	48 VDC Delta-Q, 10 ft (3 m) DC Cord	•
Rear:		48 VDC Delta-Q, 18 ft (5.5 m) DC Cord	•
Links 18 x 8.50 - 8 (4 Ply Rated)	•	Battery Charger Delete	•
USA Trail 18 x 8.50 - 8 (Load Range C)	•		
Wheel Covers:			•
Spoke, Black & Gold	•	Miscellaneous:	
Spoke, Black & Silver	•	DC/DC Converter	•
Chrome 6 in (15 cm)	•	Batteries Trojan T145	•
Chrome 8 in (20 cm)	•	Batteries Trojan T105	•
COLORS:		Batteries Trojan T105 w/ Battery Fill System	•
Body Color - Patriot Blue	•	Batteries Trojan T145 w/ Battery Fill System	•
Body Color - Hunter Green	•	LED Headlights	•
Body Color - Champagne		Brake Lights	•
Custom Body Color	•	Head Lights	•
		Hour Meter	•
Pin Stripes:		Individual Key Switch	•
Pewter	•	Unique Group Key Switch	•
Black	•	Turn Signals with 4-Way Flashers	•
Silver		State of Charge Meter	•
Seating:		OTHER PERFORMANCE:	
Seat Color - Oyster	•	Ash Tray	•
Seat Color - Tan	•	Horn	•
Seat Color - Gray	•	Rear Seat with Grab Bar	•
Seat Color - White	•	Rear View Mirror (Sun Canopy Required)	
Seat Color - Black	•	Front Disc Brakes	•
Seat Color - Brown		WEATHER PROTECTION:	
Custom Seat Color	•	Sun Canopy (Top) Black	
		Sun Canopy (Top) Beige	
Convertible Carrier		Sun Canopy (Top) White	
Seat Color - Grey	•	Windshield Flat	
Seat Color - Oyster	•	Windshield Fold Down	
Seat Color - Tan	•		
Seat Color - Brown	•	TRANSAXLE:	
Seat Color - Black	•	Limited Slip Differential	•
Seat Color - White w/ Blue	•		
Seat Color - White w/ Red	•		
Seat Color - Red w/ Black	•		