



CUSHMAN

MODEL: HAULSTER
TYPE: DIESEL POWERED MANUAL TRANSMISSION TRUCK
MODEL YEAR: 2012
Part No.: 84065



PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

Engine: 24.8 hp (18.5 kW) rated, 4 cycle, 69 cid (1123 cc) EFI, three cylinder, liquid-cooled Kubota D1105 Diesel

- **Fuel System** Indirect
- **Lubrication:** Pressurized oil system, spin-on filter 1.35 gal (5.1 L) capacity
- **Air Cleaner:** Dry cartridge with evacuator valve

Electrical: Starter, 60 amp alternator, 12 Volt maintenance free battery (590 cca, 85 minute reserve)

Acceptable Fuel: N590 Diesel fuel types - Auto / C0 / C1 / C2 / C3 / C4, BS2869 Class A2, ASTM D 975-92 Class 1, 2 and 3 & special grade 3

or

Low Sulphur Diesel (LSD S500) & Ultra Low Sulphur Diesel (USLD S15)

or

Bio-diesel - R.M.E. meeting DIN V 51606, Up to 5% RME. No mixture above 5% is acceptable

Drive Train: 4-speed manual transmission. Low creeper first gear. All forward gears synchronized

Clutch: 7.1 in (18 cm) dry single disc & pressure plate

Brakes: 4-wheel hydraulic self-adjusting drum brakes [7.9 in (20 cm) dual-servo] Dual master cylinder with remote reservoir, Mechanical hand brake

Rear Axle: Differential with hypoid gears

Capacity: Seating for 2 persons

PRODUCT OVERVIEW

Dimensions

Overall Length	136.0 in (345 cm)
Overall Width	53.0 in (135 cm)
Overall Height (No Canopy)	51.0 in (130 cm) (Top of steering wheel)
Overall Height (With ROPS)	74.0 in (188 cm)
Wheel Base	88.2 in (224 cm)
Front Wheel Track	42.0 in (107 cm)
Rear Wheel Track	44.0 in (112 cm)
Gnd Clearance @ Differential	5.0 in (13 cm)
Cargo Deck Size	47.4 in (120 cm) W x 72 in (183 cm) L
Cargo Deck Material	Diamond pattern steel

Vehicle Power

Power Source	3 Cylinder Liquid-Cooled Kubota Diesel
Horsepower (kW)	24.8 hp (18.5 kW) @ 3000 rpm (governed)
Electrical System	12 Volt starter. 60 amp alternator
Battery (Qty, Type)	One 12 Volt maintenance free
Key or Pedal Start	Key start
Air Cleaner	Dry cartridge
Lubrication	Pressurized oil system
Oil Filter	Spin-on
Cooling System	Liquid cooled
Fuel Capacity	7.0 gallon (26.5 L) tank
Transmission	Synchronized 4 Speed manual
Gear Selection	4 speeds forward - Neutral - Reverse
Gear Shift location	Dash

Rear Axle Ratio	11.16:1
Gear Shift location	Dash

Performance

Seating Capacity	2 Persons
Curb Weight	1570 lb (710 kg)
Vehicle load capacity	2400 lb (1090 kg)
Outside Clearance Circle	20.2 ft (6.2 m)
Intersecting Aisle Clearance	N/A
Speed (Governed, Level Gnd)	17.5 mph ± 0.5 mph (28 kph ± 0.8 kph)
Towing Capacity	2400 lb (1090 kg)

Steering & Suspension

Steering	Automotive power
Front Suspension	Double A-arm independent w/spring over shocks
Rear Suspension	Multiple leaf springs
Rear Axle	Differential with hypoid gears
Service Brake	4 Wheel 7.9 (20 cm) hydraulic drum
Parking Brake	Mechanical hand brake
Front Tires	USA Trail 20.5 x 8 - 10 (Load range C)
Rear Tires	USA Trail 20.5 x 8 - 10 (Load range C)

Body & Chassis

Frame	Unitized welded steel channel. E-coat finish
Front Body & Finish	Polyethelene
Rear Body & Finish	Steel with rubber fender flairs
Storage	Hinged front cowl
Standard Color	Yellow

Some items shown may be optional equipment

