

Shuttle Bus (8 seats) SB081A & SB081AB

SEEVS have a selection of new and used electric vehicles for sale. We provide silent, economical and environmentally friendly vehicles, which are all fully serviced and maintained.

All vehicles can be built to a customers' specification.



SB081AB, with gearbox



Vehicle specification: Shuttle Bus (8 seats) SB081A & SB081AB

| | |
|----------------------------------|---|
| Passenger capacity | 8 |
| Chassis | Welded tubular steel with rust-proof powder coat paint |
| Performance | |
| Range, loaded (km) | 80 |
| Maximum speed (km/h) | 28 (SB081A), 35 (SB081AB) |
| Minimum turning radius (m) | 4 |
| Maximum climbing ability, loaded | 18% (without gearbox), 25% (with gearbox) |
| Full payload weight (kg) | 1460 (SB081A), 1410 (SB081AB) |
| Overall dry weight (kg) | 830 (SB081A), 850 (SB081AB) |
| Dimensions | |
| Wheelbase (mm) | 1935 |
| Wheel tread F/R (mm) | 1210/1200 |
| Minimum clearance (mm) | 135 |
| Overall dimensions (mm: L, W, H) | 3780 x 1430 x 1940 |
| Engine | |
| Battery | Monobloc battery 6V 190AH*8 |
| Motor | Series excited 48V 3KW |
| Controller | Curtis |
| Charger | 25Amp DC output at 48 volts; input AC 220V 50HZ |
| Safety and Technology | |
| Steering | Single reduction rack and pinion |
| Suspension | Independent front wheel suspension, with two coil spring/shock absorber |
| Brakes | 4-wheels hydraulic pressure type |
| Standard Configuration | |
| Body | High impact fiber glass |
| Roof (optional) | High impact fiber glass |
| Tires | Steel 145/70 R12 |
| Windshield | One-piece, see-through laminated glass |
| Dashboard | Forward/reverse switch, ammeter, turn signal switch, headlight switch, key switch |